

### DESCRIPTION

The SR-F04 is a 2-way passive speaker system for indoor-use. Properly-designed built-in passive network provides high quality sound and high output capability. The speaker can be used for many applications as permanent and temporary installations.

### SPECIFICATIONS

|                         |   |
|-------------------------|---|
| System Type             | 2-way, Passive type, Bass-reflex type   |
| Power Handling Capacity | Continuous pink noise: 80 W<br>Continuous program: 240 W  |
| Rated Impedance         | 8 Ω   |
| Sensitivity             | 88 dB (1 W, 1 m)  |
| Frequency Response      | 80 Hz - 20 kHz  |
| Crossover Frequency     | 3 kHz   |
| Directivity Angle       | 70° Conical   |
| Speaker Component       | Low frequency: 10 cm (4") cone-type × 2<br>High frequency: Compression driver fitted with CD horn   |
| Connector               | Neutrik NL4MP × 2,<br>M4 screw terminal, distance between barriers: 11 mm (0.43")   |
| Finish                  | Enclosure: Birch plywood, black, polyurea coating<br>Grille: Steel plate, black, 40 % gloss, paint  |
| Dimensions              | 165 (W) × 400 (H) × 177 (D) mm (6.5" × 15.75" × 6.97")  |
| Weight                  | 5.8 kg (12.79 lb)   |
| Option                  | Speaker mounting bracket: HY-B0801, HY-UH04, HY-UV04<br>Ceiling mount bracket: HY-C0801<br>Speaker wall mount bracket: HY-W0801, HY-WM04<br>Speaker stand adapter: HY-ST04<br>Speaker stand: ST-34B |

### APPEARANCE

